



# Biwin PSSD

## Quick Start Guide

PR2000

BIWIN PR2000 512GB  
BIWIN PR2000 1TB  
BIWIN PR2000 2TB  
BIWIN PR2000 4TB

简体中文/繁體中文 / English

## 1: 注意事项

- 请勿随意拆解、破坏移动固态硬盘，以免造成产品无法正常工作。
- 请尽量避免在高温潮湿的环境中使用移动固态硬盘，以免对产品造成损害。

## 2: 使用指南

- 将移动固态硬盘插入 Type-C 接口内，并连接终端设备即可使用移动固态硬盘。
- 为了确保传输性能，请使用自带的转接器。
- 兼容 Mac OSX10.6+, Windows11/10/7/8, Android 4.4+, Harmony OS, 适配 iPhone 15/16系列、华为 Mate60 系列等 Type-C 接口的智能手机和平板电脑。
- 工作电压 5VDC
- 工作温度 0°C~50°C

## 3: 保修限制

- 未依操作手册使用或未依使用说明书上之指示维护所导致之故障损坏。
- 产品之毁损系受不可抗力之天灾(如水灾、火灾、地震、雷击、台风灾等)、人为故意破坏(如敲打、破裂、重击等)、计算机失调、人为疏失(如遗失、未妥善保管等)或其他非正常所导致者。
- 客户擅自或使第三人安装、添附、扩充、修改、修复、拆卸非 BIWIN 佰维授权或认可之零件所导致之毁损。
- 计算机病毒所致之产品毁损或解毒所导致之产品毁损等。
- 因物理或电子及电磁的压力或干扰，电源的不稳及误用、闪电、静电、火或其他不可抗力之因素而造成的毁损。
- 因暴露于不当的环境(包含高温或高湿度的环境)而造成的毁损。
- 因客户送至 BIWIN 佰维途中不当的运送及包装而造成的毁损。
- 提供维修服务时，维修品储存之各项数据将可能因进行修复时毁损或流失，请先行储存备份数据，BIWIN 佰维就维修品储存之各项数据恕不负责。
- 若将产品使用于研发用途或专业测试所导致之故障或毁损，不在免费保固的服务范围内。
- 因产品使用而造成磁盘数据总写入量超过产品标称的数据总写入量。
- BIWIN 佰维对用户数据不做承诺，请及时备份数据。
- PR2000 产品的 IP67 防水仅支持和产品温差小于 5°C 的水温环境，浸液损坏维修不在 BIWIN 承诺质保年限内。

## 1: 注意事項

- 請勿隨意拆解、破壞移動固態硬碟，以免造成產品無法正常工作。
- 請盡量避免在高溫潮濕的環境中使用移動固態硬碟，以免對產品造成損害。

## 2: 安裝指南

- 將移動固態硬碟插入 Type-C 接口內，併連接終端設備即可使用移動固態硬碟。
- 為了確保傳輸性能，請使用自帶的轉接器。
- 兼容 Mac OSX10.6+, Windows11/10/7/8, Android 4.4+, Harmony OS, 適配 iPhone 15/16繫列、華為 Mate60 繫列等 Type-C 接口的智慧手機和平板電腦。
- 工作電壓 5VDC
- 工作溫度 0°C~50°C

## 3: 保修限製

- 本保固服務不適用於因未依產品操作手冊或說明使用所造成之產品損壞。
- 本保固服務不適用於產品因不可抗力之天然災害(如水災、火災、地震、雷擊、颱風等)、人為破壞(如敲打、破裂、重擊等)、電源問題、人為疏失(如跌失、未妥善保管等)或其他意外所造成之產品損壞。
- 自行或第三方安裝、添附、擴充、修改、修復、拆卸未經 BIWIN 佰維授權或認可之零組件者，不得享有本保固服務。
- 本保固服務不適用於因電腦系統病毒感染或移除病毒所造成之產品損壞。
- 因物理或電子及電磁的壓力或干擾，電源的不穩及誤用、閃電、靜電、火或其他不可抗力之因素而造成的毀損。
- 因暴露於不當的環境(包含高溫或高濕度的環境)而造成的毀損。
- 因客戶送至 BIWIN 佰維途中不當的運送及包裝而造成的毀損。
- 提供維修服務時，維修品儲存之各項數據將可能因進行修復時毀損或流失，請先行儲存備份數據，BIWIN 佰維就維修品儲存之各項數據恕不負責。
- 若將產品使用於研發用途或專業測試所導致之故障或毀損，不在免費保固的服務範圍內。
- 因產品使用而造成磁盤數據總寫入量超過產品標稱的數據總寫入量。
- BIWIN 佰維對用戶數據不做承諾，請及時備份數據。
- PR2000 產品的 IP67 防水僅支持和產品溫差小於 5°C 的水溫環境，浸液損壞維修不在 BIWIN 承諾質保年限內。

## 1: Precautions

- Do not disassemble or damage the PSSD . Otherwise, the PSSD may not work properly.
- Please do not using pssd in high temp and humidity environment.

## 2: User guidance

- Use the built-in data cable to connect the hard disk to the terminal device to use the portableSSD.
- To ensure transmission performance, please use the data cable delivered with you.
- Compatible with Mac OSX10.6+, Windows11/10/7/8, Android 4.4+, Harmony OS, compatible with iPhone 15/16 series, Huawei Mate60 series and other Type-C smartphones and tablets
- Operating voltage 5VDC
- Operating temperature 0 ° C to 50 ° C

## 3: Warranty restrictions

- Failure resulting from failure to use in accordance with the manual or maintenance instructions in the manual.
- The damage of the product is caused by natural disasters of force majeure (such as flood, fire, earthquake, lightning strike, typhoon disaster, etc.), intentional damage (such as beating, cracking, hammering, etc.), computer malfunction, human negligence (such as lost, improperly kept, etc.) or other abnormal conditions.
- Damage caused by customer's authorization or by a third party to install, add, expand, modify, repair or disassemble parts not authorized or approved by BIWIN.
- Product damage caused by computer virus or detoxification caused by product damage.
- Damage caused by physical or electronic or electromagnetic pressure or interference, instability and misuse of power sources, lightning, static electricity, fire or other force majeure.
- Damage caused by exposure to improper conditions, including high temperature or humidity.
- Damage caused by improper delivery and packing on the way to BIWIN .
- When providing maintenance services, the data stored in the maintenance products may be damaged or lost during repair. Please save backup data first. BIWIN is not responsible for the data stored in the maintenance products.
- If the product is used for research and development purposes or professional testing caused by failure or damage, is not covered by the free warranty.
- The total byte written (TBW) exceeds the allowable value due to the product usage.
- BIWIN makes no commitment to user data, please backup data in time
- The IP67 waterproofing of PR2000 products only supports the water temperature environment where the temperature difference between the product and the product is less than 5 ° C, and the repair of the immersion damage is not within the warranty period of BIWIN's commitment.

## Table of Toxic and Hazardous Substances Elements and their Content

Part Name	Toxic and Hazardous Substances and Elements					
	Lead (Pb)	Mercury (Hg)	Cadmium (Cd)	Hexavalent Chromium (Cr <sup>6+</sup> )	Polybrominated Biphenyls (PBB)	Polybrominated Diphenyl Ethers (PBDE)
Casing	○	○	○	○	○	○
Circuit Board	○	○	○	○	○	○
Solder	○	○	○	○	○	○
Accessories	○	○	○	○	○	○

Note 1: "Exceeding 0.1 wt %" and "exceeding 0.01 wt %" indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.

Note 2: "○" indicates that the percentage content of the restricted substance does not exceed the percentage reference value of presence.

Note 3: The "\_" indicates that the restricted substance corresponds to the exemption.



## BIWIN STORAGE TECHNOLOGY CO., LTD.

Add: Building #4, South Zone #2, Zhongguan Honghualing Industrial Zone, NanShan, Shenzhen, China  
 Manufacturer Address: No. 8-1 Yuanhui Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou, Guangdong, China  
 Hotline: 400 8881 009  
 Website: www.biwintech.com